

KEY FEATURES

RDM, Artnet and sACN support Factory and user presets for plug and play setups Line Voltage or POE powered 1.8" OLED Display with rotary knob 99 Internal cues with fade and delay time Remote configuration via internal webpage Powder-coated aluminum ½ rack housing

SPECIFICATIONS

MOUNTING

Standalone

Truss-mount (M10 or M12 mounting hole) Wall-mount horizontal or vertical (included) DIN Rail horizontal or vertical (included) Rack-mount option (requires NET Shelf)

CONNECTIONS

Front

(4) 5pin DMX/RDM optically isolated ports Ports are bidirectional for DMX In and Output Full color OLED display Encoder w. Push to Select / Exit Button

Back

Locking Power In/Thru (2) Locking RJ45 Ethernet network connections (1x POE)

PHYSICAL

Length: 215 mm (8.5 in.) Width: 139 mm (5.5 in.) Height: 42 mm (1.65 in.) Weight: 1 kg (2.2 lbs)

ELECTRICAL

100-240 V nominal, 50/60 Hz, 10W POE 802.3af

APPROVALS/RATINGS

cETLus / CE / IP20



S

ORDERING

INCLUDED ITEMS1.5m Sectronic power cable (EU or US version)(2) Wallmount plates(2) DIN-Rail clamps

SKU US #: NRE012 EU #: 1330000065

